

• B6000 • • P6058 • P6808 • SIDE CURTAINS

PANAMA



Fabric		100% PES 1100 dtex	
Weight		900 g/m ²	DIN EN ISO 2286-2
Lacquering		1/1	
Embossing		Glossy	
Breaking strength	Warp	4000 N/5cm	EN ISO 1421-1
	Weft	4000 N/5cm	
Tear strength	Warp	600 N	DIN 53 363
	Weft	500 N	
Adhesion		100 N/5cm	EN ISO 2411
Temperature resistance		-30/+70°C	DIN EN 1876-2
Light fastness	(except white and (half-) transparent)	7-8	ISO 105 B02
Fire behavior		<100 mm/min	ISO 3795
Application		Truck/ Side curtains	

S=STANDARD - NS=This is not a standard product.
Only on request. Minimum 1.000LM

COLOR	RAL	WIDTH (cm)
		285 300 320
1001	-	□ □ □ S
1003	1014	□ □ □ S
1018	1018	□ □ □ S
1021	1021	□ □ □ S
1024	1003	□ □ □ S
1025	-	□ □ □ S
1059	1032	□ □ □ S
1622	-	□ □ □ S
1623	-	□ □ □ S
3001	-	□ □ □ S
3002	-	□ □ □ S
3015	3002	□ □ □ S
3016	-	□ □ □ S
3017	-	□ □ □ S
3018	-	□ □ □ S
3021	2008	□ □ □ S
3056	-	□ □ □ S
3057	4007	□ □ □ S
3105	-	□ □ □ S
5001	-	□ □ □ S
5003	5012	□ □ □ S
5004	5013	□ □ □ S
5007	-	□ □ □ S
5020	-	□ □ □ S
5023	-	□ □ □ S
5025	-	□ □ □ S
5026	-	□ □ □ S
5027	-	□ □ □ S
5028	-	□ □ □ S
5029	-	□ □ □ S
5030	-	□ □ □ S
5031	5010	□ □ □ S
5032	-	□ □ □ S
(New) 5033	-	□ □ □ S
5061	-	□ □ □ S
5063	5002	□ □ □ S
5104	5011	□ □ □ S
(New) 5158	-	□ □ □ S
6001	-	□ □ □ S
6002	6001	□ □ □ S
6027	6018	□ □ □ S
6028	6005	□ □ □ S
6036	-	□ □ □ S
6037	-	□ □ □ S
6038	-	□ □ □ S
6039	-	□ □ □ S
7001	-	□ □ □ S
7002	7035	□ □ □ S
7003	-	□ □ □ S
7024	-	□ □ □ S
7060	-	□ □ □ S
7071	-	□ □ □ S
7179	-	□ □ □ S
7244	7043	□ □ □ S
SILVER 7500	9006	□ □ □ S
7999	-	□ □ □ S
8020	8017	□ □ □ S
9002	-	□ □ □ S
9013	9010	□ □ □ S
(New) □	P6058/9917	- □ □ □ S
□	P6808/9917	- □ □ □ S